


Arctic Cat® Wildcat

Installation Instructions - Service Parts

Wildcat Seat Belt Buckle Update Kit

(p/n 1436-816)



■ NOTE: Read these Installation Instructions thoroughly before beginning the installation process. Retain these Installation Instructions for future reference.

Application: Specific 2013 Wildcat models

Kit includes:

p/n	QTY	DESCRIPTION
1423-183	1	Cap Screw
5506-271	1	Seat Belt Buckle
0453-858	1	Instructions

1. Remove the appropriate seat.

■ NOTE: Take note of the angle of the seat belt buckle as the new one should be installed in the same position.

2. Remove and discard the cap screw securing the existing seat belt buckle to the frame.
3. Position new Seat Belt Buckle and secure to the frame using new Cap Screw. Tighten to 60 ft-lb. See Fig. 1.

Fig. 1



ROV-219


4. Install the seat.
5. The existing seat belt buckle must be returned to Arctic Cat to receive warranty credit.



Arctic Cat® Wildcat

Instructions sur l'installation

Trousse d'actualisation de boucle de ceinture de sécurité Wildcat (p/n 1436-816)



■ REMARQUE: Lisez ces instructions sur l'usage attentivement avant de commencer la procédure d'installation. Conservez ces instructions sur l'installation pour vos références futures.

Application: Modèles Wildcat de 2013 spécifiques

La trousse inclut:

n/p	QTÉ	DESCRIPTION
1423-183	1	Vis à capuchon
5506-271	1	Boucle de ceinture de sécurité
0453-858	1	Instructions

1. Retirez le siège approprié.

■ REMARQUE: Prenez note de l'angle de la boucle de la ceinture de sécurité, puisque la nouvelle doit être installée dans la même position.

2. Retirez et jetez la vis à capuchon retenant la boucle de ceinture de sécurité actuelle au châssis.
3. Placez la nouvelle boucle de ceinture de sécurité et fixez-la au châssis au moyen de la nouvelle vis à capuchon. Serrez à un couple de 60 lb-pi. Consultez la Figure 1.

III. 1



ROV-219

4. Installez le siège.
5. La boucle de ceinture de sécurité actuelle doit être retournée à Arctic Cat afin de recevoir un crédit en vertu de la garantie.

